GENERAL NOTES 1. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS AT OMINICK Jurueyors VITA CT., SUITE D CA 95926 THE JOB SITE, AND SHALL BE RESPONSIBLE FOR CONDITIONS OF ALL WORK AND MATERIALS, INCLUDING THOSE FURNISHED BY SUB-CONTRACTORS. HE WILL IMMEDIATELY NOTIFY THE ENGINEER AND THE OWNER OF ANY DISCREPANCIES. 2. THE CONTRACT DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. UNLESS OTHERWISE SHOWN, THEY DO NOT INDICATE THE METHOD OF CONSTRUCTION. THE CONTRACTOR SHALL 293,00' A 8 89 59 52 E PROVIDE ALL MEASURES NECESSARY TO PROTECT THE STRUCTURE, WORKERS AND OTHER PERSONS DURING DEMOLITION AND CONSTRUCTION. SUCH MEASURES SHALL INCLUDE BUT NOT BE LIMITED TO BRACING, SHORING, SCAFFOLDING, PLANKING, ETC. 9 THE CONTRACTOR, AT HIS OWN EXPENSE SHALL ENGAGE PROPERLY QUALIFIED PERSONS TO DETERMINE WHERE AND HOW TEMPORARY PRECAUTIONARY MEASURES SHALL BE USED AND INSPECT SAME AT THE POWER TRANSMISSION -JOB SITE. OBSERVATION VISITS TO THE SITE BY THE ARCHITECT RTSON Inginee' TOWER (TYP.) OR ENGINEER SHALL NOT CONSTITUTE INSPECTION OF THE ABOVE ITEMS. THE ENGINEER IS NOT RESPONSIBLE FOR INSPECTION OR ACCEPTANCE OF WORKMANSHIP OR MATERIALS ON THIS PROJECT. 3. ALL MATERIALS AND WORKMANSHIP SHALL BE PERFORMED IN ACCORDANCE WITH LOCAL STANDARDS AND TO THE APPLICABLE PROVISIONS OF THE 1994 EDITION OF THE UNIFORM BUILDING CODE. ROBE 4. NOTES AND DETAILS ON THE DRAWINGS SHALL TAKE PRECEDENCE OVER THE GENERAL NOTES ON THIS SHEET. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS AND INSPECTIONS AS REQUIRED. ALL CONSTRUCTION STAKING SHALL BE PERFORMED BY ROBERTSON AND DOMINICK, CIVIL ENGINEERS AND SURVEYORS. CALL ROBERTSON AND DOMINICK 48 HOURS PRIOR TO THE START OF CONSTRUCTION AND IN 60' RIGHT-OF-WAY TO P.G. E. PER RECORDER'S -SERIAL NO. 87-19649 ADVANCE OF REQUIREMENTS FOR CONSTRUCTION STAKING ON 894-*3500.* 7. ALL EXCAVATION, BACKFILL, EARTHWORK, AND PAVING, SHALL BE IN ACCORDANCE WITH THE GEOTECHNICAL INVESTIGATION REPORT FOR THIS SITE PREPARED BY BROWN AND MILLS, INC. DATED NOVEMBER 15, 1996. IF THERE IS A DESCREPENCY BETWEEN THESE PLANS AND THAT REPORT THAT REPORT SHALL CONTROL. 8. ALL WORK SHALL CONFORM TO THE CITY OF OROVILLE STANDARDS AND THEIR REFERENCES. 9. NOTE REGARDING EARTHWORK: EVERY EFFORT HAS BEEN MADE TO PROVIDE A DESIGN TO ACHIEVE A BALANCED SITE, HOWEVER, ROBERTSON AND DOMINICK DOES NOT WARRANT OR GURANTEE A BALANCED SITE. FACTORS AFFECTING A SITE BALANCE INCLUDE SOILS FACTOR (VOLUME CHANGE), TYPE AND EXTENT OF UTILITY TRENCHES, SUBGRADE DEPTHS, PAD GRADING, AND LANDSCAPE TREATMENTS. THE CONTRACTOR SHOULD MAKE HIS OWN ESTIMATES OF EARTH-WORK QUANTITIES AND RELY ON THIS. THE CONTRACTOR SHOULD ALSO MAKE PROVISIONS FOR 6" TREE . AN IMBALANCE BY IDENTIFYING ON-SITE OR OFF-SITE DISPOSAL OR EXTRACTION SITES, AND BY PROVIDING REASONABLE CONTINGENCIES FOR PAYING FOR SUCH WORK. 20' EASEMENT FOR WATER LINES AND INCIDENTAL -PURPOSES PER RECORDER'S SERIAL NO. 86-30984 SITE CLEARING 1. REMOVE SURFACE DEBRIS. OAK . 2. DEMOLISH AND REMOVE CONCRETE, PAVING, AND ETC. IN CONSTRUCTION AREA. 3. CLEAR NEW CONSTRUCTION AREA OF PLANT LIFE AND GRASS. 4. CONFORM TO APPLICABLE CODE FOR DISPOSAL OF DEBRIS. COORDINATE CLEARING WORK WITH UTILITY COMPANIES. PROTECTION 1. PROTECT BENCH MARKS, EXISTING STRUCTURES, FENCES, ROADS, SIDEWALKS, PAVING, AND CURBS. 2. PROTECT ABOVE OR BELOW GRADE UTILITIES WHICH ARE TO REMAIN. 15' NON-EXCLUSIVE EASEMENT FOR UTILITIES -3. PROTECT ALL LANDSCAPING AND TREES THAT ARE TO REMAIN. PER RECORDER'S SERIAL NO. 85-4456 PREPARATION 1. IDENTIFY KNOWN BELOW GRADE UTILITIES. CALL UNDERGROUND SERVICES ALERT (U.S.A.) 48 HOURS BEFORE EXCAVATION. STAKE AND FLAG LOCATIONS. ROBERTSON AND DOMINICK WILL NOT ACCEPT RESPONSIBILITY FOR THE EXISTENCE OR NON-EXISTENCE OF UNDERGROUND UTILITIES. 2. IDENTIFY AND FLAG ABOVE GRADE UTILITIES. 3. MAINTAIN AND PROTECT EXISTING UTILITIES REMAINING WHICH PASS THROUGH WORK AREA. 4. UPON DISCOVERY OF UNKNOWN UTILITIES OR CONCEALED CONDITIONS, DISCONTINUE AFFECTED WORK; NOTIFY ENGINEER. PAVEMENT SECTIONS 30' RIGHT-OF-WAY FOR ROAD PURPOSES-PER 726 O.R. 61 *ASPHALT* 1. ASPHALT CONCRETE SHALL BE TYPE B. THICKNESS SHALL BE 2.5" OVER 6" CLASS 2 AGGREGATE BASE WITH 95% COMPACTION. G INDEX - 30' RIGHT-OF-WAY FOR PUBLIC UTILITIES PER RECORDER'S SERIAL NO. 87-35000 ON-SITE IMPROVEMENTS SHEET I SITE TOPOGRAPHY LEGEND SHEET 2 SITE PLAN SHEET 3 SITE/GRADING PLAN FH . FIRE HYDRANT WATER METER SCALE: I"=301 --- WATER LINE SHEET FOUND SURVEY MONUMENT -- FLOWLINE 100' EASEMENT FOR CONDUITS, LINES, TOWERS, ECT. PER 107 DEEDS, PAGE ALLAN W. CAMPBELL R.C.E. 20,244 DATE CABLE TV BOX 325 AND FOR INGRESS AND EGRESS AND PUBLIC WORKS DIRECTOR UTILITIES PER RECORDER'S SERIAL NO. UTILITY BOX 85-4457 AND FOR INGRESS, EGRESS, PUBLIC UTILITIES AND DRAINAGE PER RECORDER'S SERIAL NO. 35000 97-509 \OROVILLE\COVER JUNE 17, 1997 REVISED FEB, 1997