

REQUIREMENTS FOR STREET TREE PLANTING

NOTES:

- 1. AN APPROVED ROOT BOX SHALL BE USED WHEN PLANTING WITHIN FIVE (5') OF A HARDSCAPE (CURB GUTTER & SIDEWALK, BUILDING, ETC.).
- 2. NUMBER 15 CONTAINERS OR ONE INCH (1") OR LARGER CALIPER BAREROOT SHALL BE USED.
- 3. DO NOT PLANT WITHIN FIFTEEN (15') OF A STREET LIGHT OR FIRE HYDRANT.
- 4. THE ROOT FLARE (CROWN) SHALL BE EXPOSED AND PLANTED AT OR SLIGHTLY ABOVE FINISHED GRADE. *NOTE: ROOT FLARES ON CONTAINER TREES ARE USUALLY ONE (1") TO THREE (3") INCHES BELOW SOIL LEVEL OF THE CONTAINERS.
- 5. ON GRAFTED TREES, POINT GRAFT TOWARDS THE NORTH.
- 6. PULL ROOTS APART AND POINT THEM DOWNWARD WHILE PLANTING. THERE SHALL BE NO GIRDLING ROOTS.
- 7. REMOVE ANY NURSERY STAKES THAT CAME WITH THE TREE. INSTALL TWO, 2" DIAMETER TREE STAKES 8' IN LENGTH AND TWO TREE TIES TO SUPPORT TREE AS SHOWN IN MS-08 SHEET 1 OF 2.
- 8. IF PLANTING IN A LAWN AREA, A TRUNK PROTECTOR SHALL BE USED.
- 9. WATER IMMEDIATELY AFTER PLANTING; MAINTAIN THE TREE UNTIL ACCEPTED BY THE CITY INSPECTOR.



CITY OF OROVILLE DEPARTMENT OF PUBLIC WORKS

STANDARD FOR STREET TREE PLANTING

DRAWN BY. SG

CHRIS FRIDRICH
DIRECTOR OF PARKS AND TREES

SHEET 2 OF 2 MS-08